



PAKISTAN COUNCIL OF SCIENTIFIC & INDUSTRIAL RESEARCH

CENTRE FOR THE DEVELOPMENT OF LABORATORY EQUIPMENT



PRICE LIST

(2020)

CRUCIBLE FURNACE 1000°C Rs. 120,000/- Model No. (CF-1/02) Specifications: Temp Range: Ambient to 1000°C, Control: Digital Regulated, Tube Size: Ø 90x120 mm, Operating Voltage: 220V - 50Hz	DIGITAL CYLINDRICAL FURNACE 1000°C Model No. (DCF-1/02) Rs. 120,000/- Specifications: Temp Range: Ambient to 1000°C ± 1°C, Control: Digital, Tube Size: Ø 90x150 mm, Operating Voltage: 220V - 50Hz	CENTRIFUGE Rs. 35,125/- Model No. (CG-1/07) Specifications: Capacity 6 x 15 mL (Tubes), Speed Range 3300 RPM. (Adjustable), Power 500W, Timer 15 minutes (adjustable), and Operating Voltage: 220V - 50Hz
CYLINDRICAL WATER BATH Rs. 25,625/- Model No. (CB-1/02) Specifications: Bath Capacity: 4 L, S.S. Vessel Ø 230 x 125 mm, Control: Energy Regulator, Temp Range: Ambient to Boiling Point of Water ±5°C, Operating Voltage: 220V - 50Hz	DIGITAL CYLINDRICAL WATER BATH Model No. (DCW-1/06) Rs. 45,875/- Specifications: Capacity 4 L, S.S. Vessel Ø 230 x 125 mm, Temp Range: Ambient to Boiling Point of Water ±1°C, Control: Digital, Operating Voltage: 220V - 50Hz	DRYING OVEN 105 L (Digital) Rs. 1,95,750/- Model No. (DOD-1-105/03) Specifications: Outer Body: Powder Coated, Internal Chamber: Complete S.S, Control: Digital, Temp Range: Ambient to 220°C ± 5°C, Operating Voltage: 220V - 50Hz, Chamber Size: 520 x 450 x 450 mm.
DRYING OVEN 30L (Analogue) Rs. 95,625 Model No. (DO-1-30/02) Specifications: Temp Range: Ambient to 220°C ± 10°C, Control: Analogue, Operating Voltage: 220V - 50Hz, Complete S.S. Body, Chamber Size: 305 x 305 x 380 mm.	DRYING OVEN 60L (Analogue) Rs. 110,000/- Model No. (DO-1-60/02) Specifications: Temp Range: ambient to 220°C ± 10°C, Control: Analogue, Operating Voltage: 220V - 50Hz, Complete S.S. Body, Chamber Size: 495 x 395 x 330 mm.	DRYING OVEN 108 L (Digital) Rs. 2,25,000/- Model No. (DOD-1-108/06) Specifications: Outer Body: Powder Coated, Internal Chamber: Complete S.S, Control: Digital, Temp Range: Ambient to 220°C ± 5°C, Operating Voltage: 220V - 50Hz, Chamber Size: 520 x 455 x 450 mm.
DRYING OVEN 30L (Digital) Rs. 110,000/ Model No. (DOD-1-30/05) Specifications: Temp Range: Ambient to 220°C ± 5°C, Control: Digital, Operating Voltage: 220V - 50Hz, Complete S.S. Body, Chamber Size: 305 x 305 x 380 mm.	DRYING OVEN 60L (Digital) Rs. 130,000/- Model No. (DOD-1-60/05) Specifications: Temp Range: ambient to 220°C ± 5°C, Control: Digital, Operating Voltage: 220V - 50Hz, Complete S.S. Body, Chamber Size: 495 x 395 x 330 mm.	DRYING OVEN 130 L (Digital) Rs. 250,500/- Model No. (DOD-1-130/10) Specifications: Outer Body: Powder Coated, Internal Chamber: Complete S.S, Control: Digital, Temp Range: Ambient to 220°C ± 5°C, Operating Voltage: 220V - 50Hz, Chamber Size: 520 x 520 x 490 mm.
ELECTRO MANTLES FOR SOXHLET EXTRACTION 1L (Without Glass Apparatus) Model No. (SE-1/02) Rs. 50,875/ Specifications: Capacity: 3 Stages 1L, Temp Range: Ambient to 200°C ± 10°C, Control: Energy Regulated (Independent for each Element), Operating Voltage: 220V - 50Hz,	HEATING MANTLE 2L Rs. 25,500/- Model No. (HM-1C/05) Specifications: Body: Complete M.S, Capacity: 2L, Temp Range: 200°C, Control: Energy Regulated, Operating Voltage: 220V - 50Hz,	DRYING OVEN 256 L (Digital) Rs. 3,25,250/- Model No. (DOD-1-256/06) Specifications: Outer Body: Powder Coated, Internal Chamber: Complete S.S, Control: Digital, Temp Range: Ambient to 220°C ± 5°C, Operating Voltage: 220V - 50Hz, Chamber Size: 760 x 760 x 450 mm
ELECTRO MANTLES FOR SOXHLET EXTRACTION 500 mL (Without Glass Apparatus) Model No. (SE-1A/02) Rs. 45,500 Specifications: Capacity: 3 Stages 500 mL, Temp Range: Ambient to 200°C ± 10°C, Control: Energy Regulated (Independent for each Element), Operating Voltage: 220V - 50Hz,	HEATING MANTLE 1L Rs. 20,000/- Model No. (HM-1/02) Specifications: Body: Complete S.S, Capacity: 1L, Temp Range: 200°C, Control: Energy Regulated, Operating Voltage: 220V - 50Hz,	HORIZONTAL SHAKING WATER BATH (4 Flask) Model No. (HSW-1/06) Rs. 110,750/- Specifications: Outer Body: Powder Coated, Internal Chamber: Complete S.S, Control: Digital, Temp Range: Boiling Point of Water ± 5°C, Operating Voltage: 220V - 50Hz, Capacity: 18 L, Shaking Speed 200 Times per Min (adjustable), Shaking Stroke 20mm Horizontal.
ELECTRO MANTLES FOR SOXHLET EXTRACTION 250 mL (Without Glass Apparatus) Model No. (SE-1B/02) Rs. 40,500 Specifications: Capacity: 3 Stages 250 mL, Temp Range: Ambient to 200°C ± 10°C, Control: Energy Regulated (Independent for each Element), Operating Voltage: 220V - 50Hz,	HEATING MANTLE 500 ml Rs. 20,375/- Model No. (HM-1A/03) Specifications: Body: Complete S.S, Capacity: 500 mL, Temp Range: 200°C, Control: Energy Regulated, Operating Voltage: 220V - 50Hz,	HORIZONTAL SHAKING WATER BATH (12 Flask) Model No. (HSW-1A/06) Rs. 125,000/- Specifications: Outer Body: Powder Coated, Internal Chamber: Complete S.S, Control: Digital, Temp Range: Ambient to Boiling Point of Water ± 5°C, Operating Voltage: 220V - 50Hz, Capacity: 40 L, Shaking Speed 200 Times per Min
WATER BATH (Digital) (Regular) Model No. (GPUB-1/06) Rs. 37,500/- Specifications: Temp Range: Ambient to Boiling Point of Water ± 1°C, Control: Digital, Chamber Size: 330 x 330 x 120 mm, Operating Voltage: 220V - 50Hz.	HEATING MANTLE 250 ml Rs. 18,750/- Model No. (HM-1B/04) Specifications: Body: Complete S.S, Capacity: 500 mL, Temp Range: 200°C, Control: Energy Regulated, Operating Voltage: 220V - 50Hz,	HEATED CIRCULATING BATH 100L Model No. (HCB-1/04) Rs. 1,82,500/- Specifications: Outer Body: Powder Coated, Internal Chamber: Complete S.S, Control: Digital, Temp Range: Ambient to Boiling Point of Water ± 5°C, Operating Voltage: 220V - 50Hz, Capacity: 100 L.
HOT & COLD WATER BATH 35L Rs. 145,000/- Model No. (CS-1/06) Specifications: Outer Body: Powder Coated, Internal Chamber: Complete S.S, Control: Digital, Temp Range: +15°C to Ambient to Boiling Point of Water ± 1°C, Operating Voltage: 220V - 50Hz, Capacity: 35 L.	HOT & COLD HEAVY DUTY WATER BATH 800 L Model No. (HDWB-1/11) Rs. 5,50,250/- Specifications: Outer Body: Powder Coated, Internal Chamber: Complete S.S, Control: Digital, Temp Range: +20°C to Ambient to Boiling Point of Water ± 1°C, Operating Voltage: 220V - 50Hz,	4 IN 1 PRECISION HOT PLATE Rs. 1,95,500/- Model No. (HSW-1A/06) Specifications: Temp: Ambient to 100°C ± 0.5°C, Control: PID-Digital control (Independent for each hot plate) Hot plate size: 165 x 165 x 25mm (Teflon coated), Number of hot plates: 4 (four) Chassis: M.S. (powder coated) Operating Voltage: 220V - 50 Hz with 6 feet AC Power cord and Independent fuse holder for each plate.
MAGNETIC STIRRER HOT PLATE (Large) Model No. (MSHP-1/02) Rs. 31,250/- Specifications: Temp: Ambient to 300°C ± 5°C, Control: Thermostatic, Hot Plate Size: 165 x 165 x 25mm (Ceramic Coated), Chassis: M.S. (Powder Coated) Operating Voltage: 220 V - 50 Hz.	DIGITAL MAGNETIC STIRRER HOT PLATE Model No. (DMSHP-1/11) Rs. 50,000/- Specifications: Temp: Ambient to 300°C ± 5°C, Control: Digital, Hot Plate Size: 165 x 165 x 25mm (Ceramic Coated), Chassis: M.S. (Powder Coated) Operating Voltage: 220 V - 50 Hz.	MINI MAGNETIC STIRRER HOT PLATE Model No. (MMSHP-1A/05) Rs. 28,750/- Specifications: Temp: Ambient to 300°C ± 5°C, Control: Thermostatic, Hot Plate Size: Ø152 mm (Ceramic Coated), Chassis: M.S. (Powder Coated) Operating Voltage: 220 V - 50 Hz.
DIGITAL HOT PLATE (MINI) Model No. (DHP-1/10) Rs. 43,750/- Specifications: Temp Range: Ambient to 300°C ± 5°C, Control: Digital, Hot Plate Size: 165 x 165 x 25mm (Ceramic Coated), Chassis: M.S. (Powder Coated) Operating Voltage: 220 V - 50 Hz.	RECTANGULAR WATER BATH (Analogue) Model No. (RW-1/02) Rs. 25,750/- Specifications: Outer Body: Powder Coated, Internal Chamber: Complete S.S, Control: Thermostatic, Temp Range: Ambient to Boiling Point of Water ± 5°C, Operating Voltage: 220V - 50Hz, Capacity: 12 L.	DIGITAL RECTANGULAR WATER BATH Model No. (DRW-1/12) Rs. 37,500/- Specifications: Outer Body: Powder Coated, Internal Chamber: Complete S.S, Control: Digital, Temp Range: Ambient to Boiling Point of Water ± 5, Operating Voltage: 220V - 50Hz, Capacity: 12 L.
ROTAMANTLE 1 L Rs. 30,500/- Model No. (RM-1/02) Specifications: Temp Range: Ambient to 200°C, Control: Energy Regulated, Chassis: Complete S.S, Operating Voltage: 220 V - 50 Hz, Speed: 1200 RPM Controllable, Capacity: 1L.	ROTAMANTLE 500 ml Rs. 25,750/- Model No. (RM-1A/02) Specifications: Temp Range: Ambient to 200°C, Control: Energy Regulated, Chassis: Complete S.S, Operating Voltage: 220 V - 50 Hz, Speed: 1200 RPM Controllable, Capacity: 500 mL.	ROTAMANTLE 250 ml Rs. 22,875/- Model No. (RM-1B/03) Specifications: Temp Range: Ambient to 200°C, Control: Energy Regulated, Chassis: Complete S.S, Operating Voltage: 220 V - 50 Hz, Speed: 1200 RPM Controllable, Capacity: 250 mL.
DIGITAL ROTAMANTLE 1 L Rs. 50,750/- Model No. (DRM-1/11) Specifications: Digital Temp Indicator: Ambient to 200°C, Control: Digital Temp, Outer Body: M.S. Powder Coated, Operating Voltage: 220 V - 50 Hz, Speed Indicator: 1200 RPM digital, Controllable, Capacity: 1L.	DIGITAL ROTAMANTLE 500 ml Rs. 45,125/- Model No. (DRM-1A/11) Specifications: Digital Temp Indicator: Ambient to 200°C, Control: Digital Temp, Outer Body: M.S. Powder Coated, Operating Voltage: 220 V - 50Hz, Speed Indicator: 1200 RPM digital, Controllable, Capacity: 500 mL.	DIGITAL ROTAMANTLE 250 ml Rs. 42,500/- Model No. (DRM-1B/11) Specifications: Digital Temp Indicator: Ambient to 200°C, Control: Digital Temp, Outer Body: M.S. Powder Coated, Operating Voltage: 220 V - 50 Hz, Speed Indicator: 1200 RPM digital, Controllable, Capacity: 250 mL.
ORBITAL SHAKER Rs. 60,750/- Model No. (OS-1/02) Specifications: 09 Flask 250 mL, Control: Low / High Speed Controller, Body: M.S (Powder Coated), Operating Voltage: 220 V - 50 Hz, Speed: 80 to 350 RPM Controllable.	DIGITAL ORBITAL SHAKER Rs. 70,750/- Model No. (DOS-1/11) Specifications: 09 Flask 250 mL, Control: Low / High Speed Controller, Body: M.S (Powder Coated), Operating Voltage: 220 V - 50 Hz, Speed: 80 to 350 RPM, RPM Display: Digital RPM Indicator.	TWO STAGE DIGITAL ORBITAL SHAKER Model No. (TSDOS-1/12) Rs. 125,500/- Specifications: 18 Flask 250 mL, Control: Low / High Speed Controller, Body: M.S (Powder Coated), Operating Voltage: 220 V - 50 Hz, Speed: 80 to 350 RPM, RPM Display: Digital RPM Indicator.
OVER HEAD STIRRER Rs. 18,750/ Model No. (OHS-1/06) Specifications: Speed Range: Variable 100-2800 RPM, Stirrer Shaft Ø6mm, Stirrer Shaft Length 200mm, Body: M.S. Powder Coated, Operating Voltage: 220 V - 50 Hz.	DIGITAL OVER HEAD STIRRER Rs. 31,250/- Model No. (DOHS-1/11) Specifications: Speed Range: Variable 100-2800 RPM, Stirrer Shaft Ø6mm, Stirrer Shaft Length 200mm, Body: M.S. Powder Coated, Operating Voltage: 220 V - 50 Hz, Digital RPM Display.	DIGITAL OIL BATH MAGNETIC STIRRER Model No. (DOBMS-1/07) Rs. 125,750/- Specifications: Temp Range: 300°C ± 1°C, Control: Digital Temp, Outer Body: M.S. Powder Coated, Vessel: Complete S.S, Operating Voltage: 220 V - 50 Hz, Speed: 1200 RPM, Capacity: 4 L, Digital RPM Display.

N.B. These prices are without GST & Transportation Charges.

DIGITAL STEAM WATER BATH Model No. (DSWB-1/11) Rs. 1, 37,500/- Specifications: Control: Digital, Body: Complete S.S, Operating Voltage: 220 V - 50 Hz, Temp Range: Ambient to Boiling Point of Water, Bath Capacity: 04 L.	VORTEX MIXER Rs. 17,625/- Model No. (VM-1/07) Specifications: Speed up to 2500 RPM, Agitator cup size Ø40mm or Ø90mm, Control: Low / High Speed Controller, Body: M.S (Powder Coated), Operatine Voltage: 220 V - 50 Hz.	THERMOSTATIC DRY BATH Rs. 60,250/- Model No. (TDB-1/02) Specifications: Control: Digital, Body: M.S (Powder Coated), Temp Range: Ambient to 150°C ± 2°C, Interchangeable Heating Blocks, Operating Voltage: 220 V - 50 Hz.
MUFFLE FURNACE 1000°C Rs. 125,000/- Model No. (MF-1/02) Specifications: Temp Range: Ambient to 1000°C ± 1°C, Control: Digital Temp, Muffle Size: 100 x 120 x 220 mm, Capacity 2.6 L, Operating Voltage: 220V - 50Hz.	HIGH TEMP MUFFLE FURNACE 1200°C Model No. (HTMF-1/07) Rs. 2, 25,625/- Specifications: Temp Range: Ambient to 1200°C ± 1°C, Control: Digital Temp, Muffle Size: 100 x 112 x 220 mm, Capacity 2.6 L, Operating Voltage: 220V - 50Hz.	HIGH TEMP MUFFLE FURNACE 1200°C Model No. (HTMF-1A/13) Rs. 2, 75,000/- Specifications: Temp Range: Ambient to 1200°C ± 1°C, Control: Digital Temp, Muffle Size: 160 x 165 x 220 mm, Capacity 6 L, Operating Voltage: 220V - 50Hz.
TUBE FURNACE 1000°C Rs. 135,000/- Model No. (TF-1/02) Specifications: Temp Range: Ambient to 1000°C ± 1°C, Control: Digital Temp, Tube Size: Ø 40 x 400 mm, Operating Voltage: 220V - 50Hz.	TUBE FURNACE 1000°C (LARGE) Model No. (TF-1A/05) Rs. 2, 25,875/- Specifications: Temp Range: Ambient to 1000°C ± 1°C, Control: Digital Temp, Tube Size: Ø 65 x 800 mm, Operating Voltage: 220V - 50Hz.	HIGH TEMP TUBE FURNACE 1200°C Model No. (HTTF-1/06) Rs. 2, 25,750/- Specifications: Temp Range: Ambient to 1200°C ± 1°C, Control: Digital Temp, Tube Size: Ø 25 x 600 mm, Operating Voltage: 220V - 50Hz.
3 ZONE TUBE FURNACE 1000°C Rs. 3, 75,250/- Model No. (3ZF-1/12) Specifications: Temp Range: Ambient to 1000°C ± 1°C, Control: Digital Temp, Tube Size: Ø 60 x 500 mm, Operating Voltage: 220V - 50Hz, Three Different Thermocouples and Temperatures controller To whom It may concern: Uniformly Control the Temperature through Length without Ramping.	HEAVY DUTY HOT PLATE -300°C (Silver Top) Rs. 55,500/- Model No. (HDHP-1A/04) Specifications: Temp Range: Ambient to 300°C ± 10°C, Control: Thermostatic, Operating Voltage: 220V - 50Hz, Body: Complete S.S, Top Plate: Cast Aluminum Top Plate Ceramic Coated.	HEAVY DUTY HOT PLATE 400°C (Digital) Model No. (HDHP-1A/04)/MS Rs. 65,000/- Specifications: Temp Range: Ambient to 300°C ± 10°C, Control: Digital, Operating Voltage: 220V - 50Hz, Body: M.S (Powder Coated), Top Plate: Cast Aluminum Top Plate Ceramic Coated.
DIGITAL HEAVY DUTY HOT PLATE 400°C Model No. (DHDHP-1A/04)/MS Rs. 65,500/- Specifications: Temp Range: ambient to 400°C ± 5°C, Control: Digital, Operating Voltage: 220V - 50Hz, Body: M.S (Powder Coated), Top Plate: Cast Iron Top Plate.	HEAVY DUTY HOT PLATE 300°C (Analog) Rs. 55,875/- Model No. (HDHP-1/02)/Silver Top Specifications: Temp Range: Ambient to 300°C ± 10°C, Control: Thermostatic, Operating Voltage: 220V - 50Hz, Body: M.S. (Powder Coated), Top Plate: Cast Aluminum.	VERTICAL TUBE FURNACE 1000°C Model No. (VTF-1/12) Rs. 175,750/- Specifications: Temp Range: Ambient to 1000°C ± 1°C, Control: Digital Temp, Tube Size: Ø 38 x 400 mm, Operating Voltage: 220V - 50Hz, Uniformly Control the Temperature through Length without Ramping.
Melting Point Apparatus (Analog) Rs. 25,625/- Model No. (MP-1/02) Specifications: Temp Range: Ambient to 360°C ± 1°C, Control: Low / High Speed Controller, Temperature Indication by Hg Thermometer, Operating Voltage: 220V - 50Hz.	DIGITAL Melting Point Apparatus Rs. 50,000/- Model No. (DMP-1/07) Specifications: Temp Range: Ambient to 360°C ± 1°C, Temp Indicator Digital Display, Operating Voltage: 220V - 50Hz.	WALK THROUGH METAL DETECTOR Rs. 1, 20,000/- Model No. (WMD-02) Specifications: Detecting Power 9" each Side, Ambient to 50°C, Data Recording, Dual Beep, Video Recording VDR, Operating Voltage: 220V - 50Hz, Low Noise High Frequency, Low/High Power Efficiency.
HAND HELD METAL DETECTOR Rs. 5000/- Model No. (HMD-02) Specifications: High Penetrating Power 9", Long Battery Time, Unbreakable Box, Rechargeable backup, Video Recording VDR, Operating Voltage: 220V - 50Hz, Low Noise High Frequency, Low/High Power Efficiency.	OZONE GENERATOR Rs. 15,000/- Model No. (PESONIC-01) Specifications: Voltage: 220/240VAC 50/60 Hz, Power: 35W, Ozone Output: 150 ml/h, Timer: 40-minut Digital Timer, Air flow rate: 150 ml/h, Weight: 250 gm	Environmental Chamber L-72 Rs. 1, 35,000/- Model No. (EC-1/18) Specifications: Temp Range: 10°C to 50°C ± 1°C, Temp Indicator Digital Display, Operating Voltage: 220V - 50Hz, Dimension: 500 x 500 x 680 mm
RAMPING MUFFLE FURNACE 1000°C Model No. (RMF-1/18) Rs. 1, 35,000/- Specifications: Temp Range: Ambient to 1000°C ± 1°C, Control: Digital Temp, Muffle Size: 100 x 120 x 220 mm, Capacity 2.6 L, Operating Voltage: 220V - 50Hz, soak time, delay time, ramp time	HIGH TEMP RAMPING MUFFLES FURNACE 1200°C Model No. (RHTMF-1/18) Rs. 2, 15, 000/- Specifications: Temp Range: Ambient to 1200°C ± 1°C, Control: Digital Temp, Muffle Size: 100 x 112 x 220 mm, Capacity 2.6 L, Operating Voltage: 220V - 50Hz,soak time ,ramp time, Delay time	Growth Chamber Rs. 2, 55,000/- Model No. (GN-1/18)/L-260 Specifications: Temp Range: 10°C to 50°C ± 1°C, Temp Indicator Digital Display, Operating Voltage: 220V - 50Hz, Humidity Control Digital Dimension: 500 x 500 x 680 mm

EQUIPMENTS DEVELOPED BY PCSIR LABORATORIES COMPLEX, KARACHI.

INTELLIGENT pH METER (Digital) Model No. (I-pH-01) Rs. 40,000/- Specifications: Bench Type 0-14 pH, Accuracy ± 0.001 pH, operating voltage: 220V - 50Hz	ELECTROPHORESIS APPARATUS (Digital) Model No. (EPA-1/02) Rs. 38,500/- Specifications: 300 Volts. 100 mA, Operating Voltage: 220V - 50Hz	COOLED INCUBATOR Rs. 2, 55,000/- Model No. (CIN-1A/02) Specifications: 4 cubic feet 4°C to 40°C ± 1°C, Operating Voltage: 220V - 50Hz
PORTABLE pH METER (Digital) Model No. (P-pH-01) Rs. 18,000/- Specifications: Handy by range 0-14 pH, Accuracy ± 0.01, Operating voltage: 220V - 50Hz	WATER DE-IONIZER Rs. 23,000/- Model No. (WDI-1/02) Specifications: 6000 L/cycle, 2 L/hour, Water Quality 1µS, Operating Voltage: 220V - 50Hz	COOLED INCUBATOR Rs. 3, 55,000/- Model No. (CIN-1/02) Specifications: 4 cubic feet, -10°C to + 50°C ± 1°C, Operating Voltage: 220V - 50Hz
CONDUCTIVITY METER (Digital) Rs. 38,500/- Model No. (CMD-1/02) Specifications: Bench Type 0µS-100mS, Accuracy ± 2%, Cell Constant: 1 ± 0.05, Operating Voltage: 220V - 50Hz	PH METER (Digital) Rs. 29,000/- Model No. (pHD-1/02) Specifications: Bench Type 0-14 pH, + 700mV, Accuracy 0.01% of decimal value, Operating voltage: 220V - 50Hz	

N.B. These prices are without GST & Transportation Charges.



PAKISTAN COUNCIL OF SCIENTIFIC & INDUSTRIAL RESEARCH

Director General
PCSIR Laboratories Complex, Lahore.
 Tel: +92-42-99230697
 Fax: +92-42-99230705
 E-mail: pcsir@brain.net.pk,
 Web site: pcsir-lhr.gov.pk

Head CDLE Lahore.
 Tel: +92-42-99230788
 Fax: +92-42-99230705
 Exchange: +92-42-99230688-95
 E-mail: cdlepcsir@gmail.com
cdle@pcsir-lhr.gov.pk

Director General
PCSIR Laboratories Complex, Karachi
 Tel: +92-21-34641841
 Fax: +92-21-34641847
 E-mail: dgkcl@pcsir.gov.pk

Head CDLE Karachi.
 Tel: +92-21-34651737
 Fax: +92-21-34651737
 Exchange: +92-21-34641833-35

For, Quotation/Order please contact,
The Manager Sales & Marketing,
STEDEC, STEDEC House,
 Adj: Ismail Aivan-e-Science Building,
 Ferozepur Road, Lahore-54600
 Fax 042- 99230543 Tel: 042-99230546-99230541